



HEAT-SHEET SIZES

PRODUCT	TTL PANEL THICKNESS	AVG R-VALUE
HS-R4 ¹	1 $\frac{3}{8}$ "	4
HS-R6 ^{1,4}	1 $\frac{7}{8}$ "	6
HS-R8	2 $\frac{3}{8}$ "	8
HS-R10 ^{2,4}	2 $\frac{7}{8}$ "	10
HS-R12 ^{2,3,4}	3 $\frac{3}{8}$ "	12
HS-14 ^{2,3}	3 $\frac{7}{8}$ "	14
HSR-R10 ²	3.2"	10

1. These panels do not interlock.
2. Additional vapor barrier not required when using Type 3 EPS, per CAN/ULC S701.
3. Additional vapor barrier not required when using Type IX EPS.
4. Visit Heat-Sheet.com for more information on Heat-Sheet radiant floor insulation.

LOGIX[®]
INSULATED CONCRETE FORMS
Think With Logix™

www.logixicf.com
1-866-944-0153

The drawing represented herein is to be used as a reference guide only; the user shall check to ensure the drawing meets local building codes and construction practices by consulting local building officials and professionals, including any additional requirements. Logix reserves the right to make changes to the drawing without notice and assumes no liability in connection with the use of the drawing including modification, copying or distribution.

Drawing:
5.1.29

Date:
Dec 10/15

Page:
1/1

Title:

**HEAT-SHEET RADIANT FLOOR INSULATION
UNDER SLAB**