

Make your Logix XtraComfort™ Home MORE HIGH-WIND RESILIENT against Hurricanes and Tornadoes

1

WALLS

- Design Logix walls to the appropriate wind speed (refer to Logix whitepaper “Designing Safe Homes & Rooms”).
- Construct gable walls with Logix.
- Follow Logix-prescribed attachment recommendations.
- Use a high impact-rated synthetic stucco.

2

OPENINGS

- Install impact-rated windows (must be appropriate for the exposure category) or protect windows with impact-rated shutter products with permanent anchors (passed ASTM E1996 and E1886 for large missile test D).
- Protect sliding glass doors with impact-rated shutter products with permanent anchors (passed ASTM E1996 and E1886 for large missile test D).
- Install impact-rated entry doors or protect doors with impact-rated shutter products with permanent anchors (passed ASTM E1996 and E1886 for large missile test D).
- Install garage doors that meet design pressures associated with design wind speeds (ASCE 7-05 or ASCE 7-10).

3

OVERHANGS

- Gable overhangs should not be vented.
- Center-brace at mid-span box type all soffit and gable overhangs.



4

ROOF

- Truss design for high wind loads per exposure.
- Consider a 6/12 roof pitch or a 4-sided hipped roof for maximum wind deflection and minimum roof lift.
- Use machine-rated 2400 psi framing lumber for roof trusses (2x stronger than regular framing).
- To build a roof deck, use 7/16" OSB or plywood or 5/8" zip system.
- Use oversized truss hangers.
- Seal the roof deck for high wind conditions (refer to recommendations from Fortified Homes).
- Flash roof penetrations and valleys.
- Install wind-rated under-layment.
- Install a high wind-rated roof cover (meets ASTM D7158 Class H).
- Fasten shingles with 8D ring shank nails 6" to 4" o/c.
- Install ridge and off ridge vents rated for water intrusion resistance [meet Florida Code TAS (100) A].
- Add strength from the underside with closed cell polyurethane foam (minimum core density 1.5-3.0 L B/CI, meets ASTM D1622).

5

OTHER

- Ensure chimney is adequately connected to the roof structure.
- Ensure porches and car ports are adequately connected to resist uplift (to beam/wall, from beam to beam and column to structure below).

6

SAFE ROOM

- Construct a FEMA-compliant in-home or outside safe room with Logix (an in-home safe room built into a corner can use two existing Logix exterior walls).

LOGIX®
INSULATED CONCRETE FORMS

Build Anything Better.

The suggestions in this document are intended to be thought-starters only. Be sure to obtain the approval of your local building department, your designers and builder before implementing any suggestion contained herein. Logix Insulated Concrete Forms Ltd. does not warrant or in any way guarantee the successful performance of any suggestion contained in this document.

888.415.6449 ■ LogixICF.com

Copyright 2016 Logix Insulated Concrete Forms Ltd.