

THE HEARTLAND 1100



ESTIMATED ANNUAL ENERGY CONSUMPTION

MODELLING INPUTS MODELLING RESULTS	ESTIMATED ANNUAL ENERGY CONSUMPTION	Primary Space Heating (MJ)	21,706
		Secondary Space Heating (MJ)	4583
		Primary DHW Heating (MJ)	17,505
		HRV or ERV and Fans (MJ)	4006
		Air Conditioner (MJ)	997
		TOTAL ENERGY CONSUMPTION (GJ)	74.4
		ESTIMATED ANNUAL ENERGY COST	\$1,592
		Est. Natural Gas Consumpton (m3)	-
		Est. Electricity Consumption (kWh)	20,672
		Ceiling Below Attic	Effective R59.22
		Walls Above Grade (exterior)	"Effective R24.15 (Logix Pro ICF)"
		Slab-on-grade with an Integral Footing	Effective R21.12
		Windows & Sliding Glass Doors (W/m2•K)	U-Value: 0.63
		Airtightness	"< 1.56 ACH @ Pa (Assumed - No Air Test Required)"
	HVAC	Ventilation	60% SRE
		Secondary Space Heating Equipment	Electric Resistance (backup)
		Primary Space Heating & Space Cooling Equipment	ASHP (3.31 HEAT COP/ 3.85 COOL COP)
	DHW	Water Heater	0.84 EF (electric)

NOTES

- ci = continuous insulation.
- o.c. = on-centre.

 Modelling is based on C1 prescriptive package from SB-12 in the 2012 Ontario Building Code.
- Modelling was completed utilizing HOT2000 v11.9. Imperial U-values and R-values have been noted in
- Estimated operating cost is based on an average of the Ontario off-peak, mid-peak, and on-peak electricity rates.
- This is a model only and is provided for illustration purposes only. Actual energy consumption will vary depending on lifestyle, location, orientation, air tightness detailing, and any number of factors.

