

## **THE HEARTLAND 950**



## **ESTIMATED ANNUAL ENERGY CONSUMPTION**

| MODELLING INPUTS MODELLING RESULTS | ESTIMATED ANNUAL ENERGY CONSUMPTION | Primary Space Heating (MJ)                      | 16,102  |
|------------------------------------|-------------------------------------|---|---|
|                                    |                                     | Secondary Space Heating (MJ)                    | 5078  |
|                                    |                                     | Primary DHW Heating (MJ)                        | 17,505  |
|                                    |                                     | HRV or ERV and Fans (MJ)                        | 4964  |
|                                    |                                     | Air Conditioner (MJ)                            | 1522  |
|                                    |                                     | TOTAL ENERGY CONSUMPTION (GJ)                   | 70.8  |
|                                    |                                     | ESTIMATED ANNUAL ENERGY COST                    | \$1,514   |
|                                    |                                     | Est. Natural Gas Consumpton (m3)                | -   |
|                                    |                                     | Est. Electricity Consumption (kWh)              | 19,665  |
|                                    |                                     | Ceiling Below Attic                             | Effective R59.22                                      |
|                                    |                                     | Walls Above Grade (exterior)                    | "Effective R24.15 (Logix Pro ICF)"                    |
|                                    |                                     | Slab-on-grade with an Integral Footing          | Effective R21.12                                      |
|                                    |                                     | Windows & Sliding Glass Doors (W/m2•K)          | U-Value: 0.63   |
|                                    |                                     | Airtightness                                    | "< 1.56 ACH @ Pa<br>(Assumed - No Air Test Required)" |
|                                    | HVAC                                | Ventilation                                     | 60% SRE   |
|                                    |                                     | Secondary Space Heating Equipment               | Electric Resistance (backup)                          |
|                                    |                                     | Primary Space Heating & Space Cooling Equipment | ASHP ( 3.31 HEAT COP/ 3.85 COOL COP)                  |
|                                    | DHW                                 | Water Heater                                    | 0.84 EF (electric)                                    |

## **NOTES**

- ci = continuous insulation.
- o.c. = on-centre.

  Modelling is based on C1 prescriptive package from SB-12 in the 2012 Ontario Building Code.
- Modelling was completed utilizing HOT2000 v11.9. Imperial U-values and R-values have been noted in
- Estimated operating cost is based on an average of the Ontario off-peak, mid-peak, and on-peak electricity rates.
- This is a model only and is provided for illustration purposes only. Actual energy consumption will vary depending on lifestyle, location, orientation, air tightness detailing, and any number of factors.

